AMENDMENTS TO THE CLAIMS

Docket No.: 31229-232408

This listing of the claims will replace all prior versions and listings of claims in the application.

- 1. (Original) A method of attaching a load carrier fixing member to a vehicle, the method comprising applying adhesive to the vehicle roof and/or the fixing member, and attaching the fixing member to the vehicle, for subsequent attachment of a load carrier to the fixing member, the fixing member comprising a surface for adhering to the vehicle, characterized in that the surface for adhering to the vehicle comprises at least one undercut and/or dovetail.
 - 2. (Cancelled)
- 3. (Original) A method as claimed in claim 1, wherein the surface for adhering to the vehicle is indented.
 - 4. (Cancelled)
- 5. (Currently amended) A method as claimed in <u>claim 1</u> any one of the preceding elaims, wherein a load carrier for attaching to the load carrier fixing member is a roof rail or roof rack.
- 6. (Original) A method as claimed in claim 5, wherein the load carrier is a roof rack and the load carrier fixing member is a roof rail.
- 7. (Currently amended) A method as claimed in <u>claim 1 any one of the preceding</u> elaims, wherein the load carrier is attached directly to one or more fixing members.

8. (Currently amended) A method as claimed in <u>claim 1 any one of the preceding</u> elaims, wherein a fixing member trim finisher is attached to a non adhered side of the fixing member.

Docket No.: 31229-232408

- 9. (Original) A method as claimed in claim 8, wherein the fixing member trim finisher is removably attached to the fixing member.
- 10. (Currently amended) A method as claimed in <u>claim 1 any one of the preceding</u> elaims, wherein the fixing member comprises at least one gap hider.
- 11. (Original) A method as claimed in claim 8, wherein the at least one gap hider is positioned between the fixing member and the vehicle body roof.
- 12. (Currently amended) A method as claimed in <u>claim 1</u> any one of the preceding elaims, wherein the method further comprises pre-treating the vehicle, including cleaning a part of the vehicle to be worked on, and/or the use of an abrasive material.
- 13. (Currently amended) A method as claimed in <u>claim 1 any one of the preceding</u> elaims, wherein the fixing member is secured in position using one or more locating members, which is/are shaped to hold the fixing member in the required position relative to the vehicle roof to receive a load carrier.
- 14. (Currently amended) A method of attaching a load carrier fixing member to a vehicle, the method comprising applying adhesive to the vehicle roof and/or said fixing member, and attaching said fixing member to the vehicle, the surface for adhering to the vehicle comprises at least one undercut and/or dovetail.

- Docket No.: 31229-232408
- 15. (Original) A method as claimed in claim 14, wherein the load carrier fixing member.
- 16. (Original) A method as claimed in claims 14, wherein the load carrier fixing member is a trim finisher.
- 17. (Currently amended) A kit for fitting a load carrier fixing to a vehicle, the kit comprising a fixing member as defined in <u>claim 1 any one of the preceding claims</u>, and adhesive.
- 18. (Original) A fixing member for a vehicle load carrier attachment comprising an adhesive receiving portion and a load carrier fixing portion, wherein the load carrier fixing portion is operable to receive a fixing element of the vehicle load carrier attachment.
- 19. (Original) A fixing member as claimed in claim 18, wherein the adhesive receiving portion incorporates at least one recess adapted to receive adhesive.
- 20. (Currently amended) A fixing member as claimed in claim 18-or 19, wherein the adhesive receiving portion is a locating portion having roof engaging projections, which are operable to locate the locating portion relative to a roof recess.
- 21. (Currently amended) A fixing member as claimed in claim 18any one of claims 18 to 20, wherein a portion of said fixing member is adapted to be hooked under a part of the vehicle roof.
- 22. (Original) A method of securing a vehicle load carrier to a vehicle roof using adhesive and mechanical attachment to the vehicle roof.